

Clicwall® FR

Decorative wallcovering, fire retardant.

Melamine faced fire-retardant and non-structural MDF-LA FR board with Uniclic profile, available in an extensive range of high-quality UNILIN-Evola designs. Clicwall FR is suitable for dry conditions, service class 1, mainly used for separation walls and wall linings. This fire-retardant product is B-s2,d0 certified, B-s1,d0 available on request. Clicwall FR is made from 100% circular wood from waste flows from the wood industry, sustainable forestry or verge management.

Applications

- Separation walls
- Wall linings

Characteristics

- MDF-LA FR (EN 14322)
- A wide selection of designs
- Perfect for intensive use
- Quick installation for an immediate stylish result
- Fire retardant
- Tongue and groove
- 100% circular wood



UNILIN

Clicwall® FR

Applications

Melamine faced, fire retardant and non-structural MDF board for seperation walls and wall linings.
Long sides provided with Uniclic profile resulting in a fast and easy click system.
Scratch resistant, impact proof and highly hygiënic which makes Clicwall FR suitable for projects in retail, hotel, holiday homes, modular units, office, senior homes, eductation, etc.
Clicwall FR can be used in non humid conditions (service class 1).
Clicwall FR 10 mm (thickness) is conform Euroclass B-s2,d0; 12mm results in Euroclass B-s1,d0.

Available dimensions / thicknesses

Dimensions: Net/gross (HxWxD):
- Clicwall standard B-s2,d0 : 2785x600x10mm / 2785x618x10mm; 13kg
- Clicwall standard B-s1,d0 : 2785x600x12mm / 2785x618x12mm; 15,5kg

Other dimensions: on request.

Certificates

UNILIN Division Panels is actively committed to sustainable forest management. Clicwall FR is standard PEFC labelled and is available on demand with FSC labeling.

Carb II / TSCA VI compliant.

UNILIN, division panels
Ingelmunstersteenweg 229 – 8780 Oostrozebeke – Belgium
info.panels@unilin.com / www.unilinpanels.com

24.01.2020