

Clicwall® MR

Decorative wallcovering, moisture resistant.

Melamine faced moisture-resistant and non-structural MDF.H board with Uniclic profile, available in an extensive range of high-quality UNILIN-Evola designs. Clicwall MR is suitable for humid conditions, service class 2, mainly used for separation walls and wall linings. Clicwall MR is made from 100% circular wood from waste flows from the wood industry, sustainable forestry or verge management.

Applications

- Separation walls
- Wall linings

Characteristics

- MDF.H (EN 14322)
- A wide selection of designs
- Perfect for intensive use
- Quick installation for an immediate stylish result
- Tongue and groove
- 100% circular wood



UNILIN

Clicwall® MR

Applications

Melamine faced, moisture resistant and non-structural MDF board for seperation walls and wall linings.
Long sides provided with Uniclic profile resulting in a fast and easy click system.
Scratch resistant, impact proof and highly hygiënic which makes Clicwall MR suitable for projects in retail, hotel, holiday homes, modular units, office, senior homes, eductation, etc.
Clicwall MR is conform Euroclass D-s2,d0 (non fire retardant application) and can be used in humid conditions (service class 2).

Available dimensions / thicknesses

Dimensions: Net/gross (HxWxD):
- Clicwall standard: 2785x600x10mm / 2785x618x10mm; 13kg/panel
  Other dimensions: on request

Certificates

UNILIN Division Panels is actively committed to sustainable forest management. Clicwall MR is standard PEFC labelled and is available on demand with FSC labeling.

Carb II / TSCA VI on demand.

UNILIN, division panels
Ingelmunstersteenweg 229 – 8780 Oostrozebeke – Belgium
info.panels@unilin.com / www.unilinpanels.com

24.01.2020