



Clicwall[®]

Decorative wallcovering

Melamine faced and non-structural MDF board with Uniclic profile, available in an extensive range of high-quality UNILIN-Evola designs. Clicwall is suitable for dry conditions, service class 1, mainly used for separation walls and wall linings. Clicwall is made from 100% circular wood from waste flows from the wood industry, sustainable forestry or verge management.

Applications

- Separation walls
- Wall linings

Characteristics

-  MDF (EN 14322)
-  A wide selection of designs
-  Perfect for intensive use
-  Quick installation for an immediate stylish result
-  Tongue and groove
-  100% circular wood



Clicwall®

Applications

Melamine faced non-structural MDF board for separation walls and wall linings. Long sides provided with Uniclic profile resulting in a fast and easy click system. Scratch resistant, impact proof and highly hygienic which makes Clicwall suitable for projects in retail, hotel, holiday homes, modular units, office, senior homes, education, etc. Clicwall is conform Euroclass D-s2,d0 (non fire retardant application) and can be used in non humid conditions (service class 1).

Available dimensions / thicknesses

Dimensions: Net/gross (HxWxD):

- Clicwall standard: 2785x600x10mm / 2785x618x10mm; 13kg/panel
- Clicwall high panels: 3500x600x10mm / 3500x618x10mm; 16kg/panel

Other dimensions: on request.

Certificates

UNILIN Division Panels is actively committed to sustainable forest management. Clicwall is standard PEFC labelled and is available on demand with FSC labeling.

Carb II / TSCA VI on demand.