



UNILIN Evola-Belspan[®]

Melamine faced non-structural chipboard for interior- and furniture available in an extensive range of UNILIN Evola designs.

UNILIN Evola-Belspan is a melamine faced non-structural P2 chipboard. The board is suitable for dry conditions, service class 1, mainly used for interior and furniture. UNILIN Evola-Belspan is made from 100% circular wood: up to 85% postconsumer wood, supplemented by wood from waste flows from the wood industry, sustainable forestry or verge management.

Applications

- Interior design
- Furniture production
- Vertical applications

Characteristics



P2



Melamine faced chipboard



100% circular



UNILIN Evola-Belspan®

Applications

UNILIN Evola-Belspan is applied in different applications for interior and furniture design. The board is mainly used for vertical applications.

Advantages

Available from stock in all UNILIN Evola stockrange decors. In perfect colour match with HPL & edging tape for all UNILIN Evola stockrange decors

- Easy to clean
- Resistant to UV light
- Budget friendly
- Easy to process
- 100% circular board

Technical specifications

Performance characteristics	Unit	Average values					
	mm	>6-13	>13-20	>20-25	>25-32	>32-40	>40
Bending strength EN 310	N/mm ²	11	11	10,5	9,5	8,5	7
Bending stiffness EN 310	N/mm ²	1600	1600	1500	1350	1200	1050
Internal bond EN 319	N/mm ²	0,35	0,35	0,30	0,25	0,20	0,20
Water vapour permeability	Wet %	16	16	16	15	15	15
	Dry %	50	50	50	50	50	50

UNILIN Evola-Belspan meets the general requirements and comes under formaldehyde emission class E1 as described in Table 1 of EN Standard 622-1.

Finish

The melamine faced board is possible to have in combination with a wide variety of designs.

The wood decors not only look incredibly lifelike, also the structures feel particularly authentic. Combined with plain colours, basis on international trends, the designs deliver unprecedented freedom in creativity for interior projects.

Available dimensions / thicknesses*

All designs from the UNILIN Evola stock collection are available in combination with Belspan P2 board.

Standard sizes are 2800x2070 and/or 2500x1250 and/or 3050x1250.

Thicknesses 18mm and 19mm are immediately available from stock for all designs from UNILIN Evola stock collection in size 2800x2070.

Other thicknesses from our service program (8 till 28mm) are ready to pick up within maximum 10 working days.

All info on dimensions and sizes is available in our price- or stocklists.

Certificates

UNILIN Division Panels is actively committed to sustainable forest management. UNILIN Evola-Belspan is available in PEFC 75% and on demand with FSC labelling.