

Tarauds machine rectifiés

00103 | 00403




DETAILS :

 HSS-Co acier à 5% cobalt
 ISO 529 | NFE 66103 | Pas métrique

Aspect : Blanc

Tolérance : 6 H

Conditionnement : En boîte plastique individuelle



UTILISATION :


- Tour les aciers < 800 N/mm²

Ø	x	pas	Ø perçage	L1	L2	Ø	x	pas	Ø perçage	L1	L2
2	x	40	1,6	12	41	12	x	150	10,5	29	89
2,5	x	45	2,05	13	44	12	x	175	10,2	29	89
3	x	50	2,5	11	48	14	x	100	13	30	95
3	x	60	2,4	11	48	14	x	125	12,75	30	95
3,5	x	60	2,9	13	50	14	x	150	12,5	30	95
4	x	70	3,3	13	53	14	x	200	12	30	95
4	x	75	3,25	13	53	16	x	100	15	32	102
5	x	80	4,2	16	58	16	x	125	14,75	32	102
5	x	90	4,1	16	58	16	x	150	14,5	32	102
6	x	100	5	19	66	16	x	200	14	32	102
7	x	100	6	19	66	18	x	150	16,5	37	112
8	x	100	7	22	72	18	x	250	17,5	37	112
8	x	125	6,8	22	72	20	x	150	18,5	37	112
9	x	125	7,8	22	72	20	x	250	17,5	37	112
10	x	100	9	24	80	22	x	250	19,5	38	118
10	x	125	8,8	24	80	24	x	300	21	45	130
10	x	150	8,5	24	80	27	x	300	24	45	135
12		100	11	29	89	30		350	26,5	48	138
12		125	10,75	29	89						

Entrée : Type B GUN


Goujure : Droite

Trou : Débouchant



Coffrets 00403

Ø mm	pcs/étui	Ø mm	pcs/étui
3x50	1	10x150	1
4x70	1	12x175	1
5x80	1	14x200	1
6x100	1	16x200	1
7x100	1	18x250	1
8x125	1	20x250	1



Coffrets 00103

 Réf.
 00103 TAMA

 7 forets HSS Ø 2,5 - 3,3 - 4,2 - 5 - 6,8 - 8,5 - 10,2 mm
 7 tarauds machine
 3x50 - 4x70 - 5x80 - 6x100 - 8x125 - 10x150 - 12x175
 + 1 tourne-à-gauche n° 1 1/2
