



M12

M12 FDDXKIT-202X

M12 FUEL™ INSTALLATION DRILL/DRIVER WITH INTERCHANGEABLE HEADS

- ◆ High performance compact 4-in-1 installation drill for extreme versatility
- ◆ Removable chuck system with 4 different heads for multiples of applications



| | |
|--------------------------------|---|
| No load speed (rpm) | 0 - 400/ 0 - 1600 |
| Chuck capacity (mm) | 10 |
| Max. drilling wood/ steel (mm) | 28/ 10 |
| Max. torque (Nm) | 34 |
| Standard equipment | 10 mm metal chuck, right angle attachment, offset attachment and 6mm hex attachment |



4 058546 229245



M12

M12 FDDXKIT-202X

M12 FUEL™ INSTALLATION DRILL/DRIVER WITH INTERCHANGEABLE HEADS

- ◆ High performance compact 4-in-1 installation drill for extreme versatility
- ◆ Removable chuck system with 4 different heads for multiples of applications



| | |
|--------------------------------|---|
| No load speed (rpm) | 0 - 400/ 0 - 1600 |
| Chuck capacity (mm) | 10 |
| Max. drilling wood/ steel (mm) | 28/ 10 |
| Max. torque (Nm) | 34 |
| Standard equipment | 10 mm metal chuck, right angle attachment, offset attachment and 6mm hex attachment |



4 058546 229245



M12

M12 FDDXKIT-202X

M12 FUEL™ INSTALLATION DRILL/DRIVER WITH INTERCHANGEABLE HEADS

- ◆ High performance compact 4-in-1 installation drill for extreme versatility
- ◆ Removable chuck system with 4 different heads for multiples of applications



| | |
|--------------------------------|---|
| No load speed (rpm) | 0 - 400/ 0 - 1600 |
| Chuck capacity (mm) | 10 |
| Max. drilling wood/ steel (mm) | 28/ 10 |
| Max. torque (Nm) | 34 |
| Standard equipment | 10 mm metal chuck, right angle attachment, offset attachment and 6mm hex attachment |



4 058546 229245



M12

M12 FDDXKIT-202X

M12 FUEL™ INSTALLATION DRILL/DRIVER WITH INTERCHANGEABLE HEADS

- ◆ High performance compact 4-in-1 installation drill for extreme versatility
- ◆ Removable chuck system with 4 different heads for multiples of applications



| | |
|--------------------------------|---|
| No load speed (rpm) | 0 - 400/ 0 - 1600 |
| Chuck capacity (mm) | 10 |
| Max. drilling wood/ steel (mm) | 28/ 10 |
| Max. torque (Nm) | 34 |
| Standard equipment | 10 mm metal chuck, right angle attachment, offset attachment and 6mm hex attachment |



4 058546 229245